TOUR SERIES LED SUPER WASH

Технические характеристики

Питание: 100 - 240 В, 50-60 Гц
Светодиоды: 60 x 3 Вт светодиодов
(красные, зеленые, синие, белые)
Управление: DMX-512, 13 каналов
Размеры: 400 x 310 x 390 мм
Вес: 6 кг

- движение по панораме: 540° (16 бит)
- движение в вертикальной плоскости: 265° (16 бит)
- строб-эффект: 1...25 всп./сек.
- единый диммер и блэкаут для всех цветовых комбинаций
- уникальная система смешивания цветов, эффект радуги
- LCD-дисплей, встроенный в корпус прибора
- 8 встроенных программ, работающих независимо от DMX-контроллера
- угол раскрытия луча: 28°, (опциональная линза позволяет получать различные углы)
- встроенный беспроводной интерфейс
- встроенный источник питания, позволяющий производить программирование прибора без подключения к электросети
- RDMX: удаленное назначение DMX-адресов, удаленное управление включением/выключением лампы



Different beam angle lens on demand





	1	2	3	4	5	6	7	8	9	10	11	12	13
%	R	G	B	W	Pan	Tilt	Scan Speed	Strobe	Dimming	Rainbow	Auto Program	Pan High Resolution	Tilt High Resolution
100%	RED	GREEN	BLUE	WHITE			Normal				program 7	16 bit pan move	16 bit tilt move
75%							Blackout by moving	Random Strobe			program 1		
50%							Min	Pulse-effect in sequences		Crossfading Colours	No Function		
25%							Moving speed			Rainbow Colours	Scan Motor Rest		
0%							Max			No Function	All Motor Rest		
											No Function		
											Color & Gobo change to any position		
											Normal		

Опция
беспроводной DMX-интерфейс
W-512T

ROXTON lighting